NORTH AMERICAN REFRIGERATION

CAKE DISPLAY CASE

Model Numbers: CD48-3, CD60-3, CD72-3

CD72-3
Dimensions: 70.875" x 28.75" x 55.125"

Featuring:

- Exterior: Stainless steel floor and walls, standard. Sliding doors.
- 12V LED lighting system, safe for users to operate.
- Tempered glass to avoid injury by broken glass.
- Preinstalled hidden caster design.
- Refrigeration system maintains temperatures between 36°F and 43°F (2°C to 6°C).
- Refrigerant: HYDRO-CARBON R290.
- Shelves: Adjustable glass shelves provide extra large viewing area to maximize bakery product presentation.
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- Removable installation board makes it easy to access condenser coil for cleaning and service.
- NSF-7 compliant for open food product.

REFRIGERATED CAKE DISPLAY CASE - PRODUCT SPECIFICATIONS

Model	Doors	Shelves	Cabinet Dimensions (inches)			CAP. CU. FT. LITER	HP	Voltage	Amps	NEMA Config.
			W	D	H					
CD48-3	2	3	47 1/4	28 3/4	55 1/8	19.4	1/3+	115/60/1	7.5	5-15P
CD60-3	2	3	59 1/8	28 3/4	55 1/8	25	1/2+	115/60/1	8.3	5-15P
CD72-3	2	3	70 7/8	28 3/4	55 1/8	30	1/2+	115/60/1	8.5	5-15P

Specifications subject to change without notice • Voltage 230-240/50/1 available • Plug type varies by country.

© 2016 North American Restaurant Equipment

(401) 639-3271 • www.northamericanrefrigeration.com

Intertek CONFORMS TO UL STD 471 CERTIFIED TO CSA STD C22.2 NO 120

Intertek CONFORMS TO NSF/ANSI STD 7

HYDRO-CARBON R290 NATURAL REFRIGERANT